

70514

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Parts 121, 125

[Docket No. FAA-1999-6140; Amendment Nos. 121-271 and 125-32] - 3

RIN 2120-AG88

Revisions to Digital Flight Data Recorder Requirements for Airbus Airplanes; Correction

AGENCY: Federal Aviation Administration (FM), DOT.

ACTION: Final Rule; correction.

SUMMARY: The FAA published a final rule in the Federal Register on August 24, 1999, (64 FR 46117). The rule

amended the flight data recorder regulations by adding language to allow certain Airbus airplanes to record certain data parameters using resolution and sampling requirements that differed slightly from the regulation. This document makes certain corrections to Appendix E to Part 125, Airplane Flight Recorder Specifications.

EFFECTIVE DATE: August 17, 1999.

FOR FURTHER INFORMATION CONTACT: Gary E. Davis, Air Carrier Operations Branch (AFS-201), Flight Standards Service, Federal Aviation Administration, 800 Independence Avenue, SW., Washington, DC 20591, telephone (202) 267-8166.

SUPPLEMENTARY INFORMATION: On August 24, 1999, the FM published an amendment to the flight data recorder requirements of 14 CFR Parts 121 and 125 (64 FR 46117). In the amendment to Appendix E to Part 125, Airplane Flight

Recorder Specifications, one parameter listing was inadvertently omitted. This action corrects that omission.

correction

In FR Doc. 99-21783, published on August 24, 1999 (64 FR 46117), make the following correction:

On page 46122, third column, in Appendix E to Part 125, Airplane Flight Recorder Specifications, insert parameter 21, in numerical order, to read as follows:

• □ • • •

Appendix E to Part 125—Airplane Flight Recorder Specifications

The recorded values must meet the designated range, resolution, and accuracy requirements during dynamic and static conditions. All data recorded must be correlated in time to within one second.

Parameters	Range	Accuracy (sensor input)	Seconds per sampling interval	Resolution	Remarks
21. Leading Edge Flap or Cockpit Control Selection ¹¹ .					

• * •

Issued in Washington, DC on January 12, 2000.

Donald P. Byrne,

*Assistant Chief Counsel, Regulations
Division.*

[FR Doc. 00-1056 Filed 1-13-00; 8:45 am]

BILLING CODE 4910-13-M

[4910-13]

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Parts 121, 125

[Docket No. **FAA-1999-6140**; Amendment Nos. **121-271 & 125-32**]

RIN 2120-AG88

Revisions to Digital Flight Data Recorder Requirements for Airbus Airplanes; Correction

AGENCY : Federal Aviation Administration (FAA), DOT.

ACTION: Final Rule; correction.

SUMMARY: The FAA published a final rule in the Federal Register on August 24, 1999, (64 FR 46117). The rule amended the flight data recorder regulations by adding language to allow certain Airbus airplanes to record certain data parameters using resolution and sampling requirements that differed slightly from the regulation. This document makes certain corrections to Appendix E to Part 125, Airplane Flight Recorder Specifications.

EFFECTIVE DATE: August 17, 1999.

FOR FURTHER INFORMATION CONTACT: Gary E. Davis., Air Carrier Operations Branch (AFS-201), Flight Standards Service, Federal Aviation Administration, 800 Independence Avenue, SW., Washington, DC 20591, telephone (202) 267-8166.

2 EP 1/12/00

SUPPLEMENTARY INFORMATION: On August 24, 1999, the FAA published an amendment to the flight data recorder requirements of 14 CFR Parts 121 and 125 (64 FR 46117). In the amendment to Appendix E to Part 125, Airplane Flight Recorder Specifications, one parameter listing was inadvertently omitted. This action corrects that omission.

Correction

In FR Doc. 99-21783, published on August 24, 1999 (64 FR 46117), make the following correction:

On page 46122, third column, in Appendix E to Part 125, Airplane Flight Recorder Specifications, insert parameter 21, in numerical order, to read as follows:

* * * * *

Appendix E to Part 125 - Airplane Flight Recorder Specifications

The recorded values must meet the designated range, resolution, and accuracy requirements during dynamic and static conditions. All data recorded must be correlated in time to within one second.

Parameters	Range	Accuracy (sensor input)	Seconds per sampling interval	Resolution	Remarks
* * * * *					
21. Leading Edge Flap or Cockpit Control Selection?	* * *	* * *	* * *	* * *	* * *
* * * * *					

* * * * *

3 EP 1/12/00

Issued in Washington, DC on January 12, 2000.



Donald P. Byrne

Assistant Chief Counsel, Regulations Division